# KStrong® Wrangler Jr.™ 60 ft. Adjustable 2-person Capacity Horizontal Lifeline System

## DESIGN

KStrong® Wrangler™ 60 ft. Adjustable 2-Person Capacity Lightweight Quick Set-up Horizontal Lifeline System. Includes installation carabiner at each end, tension indicator two (2) anchor straps and a fall/impact indicator.



Model: UFA40012

• Temporary horizontal lifeline consisting Ø5/8" Kernmantle rope having a terminated eye at one end of the lifeline and other with a specially designed tensioner.

• Provided with two (2) O Rings to facilitate the workers ease of movement along the horizontal lifeline.

## SPAN LENGTH

Minimum: 16.40 ft. | Maximum: 60 ft.

#### MATERIAL

O Ring: Alloy steel Tensioner: Alloy Steel

#### MINIMUM BREAKING STRENGTH

5600 lbs.

### WEIGHT

17.03 lbs. ± 0.02 lbs. (7725 gm ± 10 gm)

#### **RELEVANT STANDARDS**

Meets or Exceeds OSHA and applicable ANSI Z359.1-2007, EN 795:2012 TYPE C, and TS16415:2013 TYPE C

Carabiner OS/8" (16mm) Kernmantle Rope OS/8" (16mm) Kernmantle Rope Tensioner Anchorage

O-ring

Meets or Exceeds applicable ANSI Z359.1-2007, EN 795:2012 TYPE C, and TS16415:2013 TYPE C