KStrong® Handy Line™ 60 ft. Adjustable 2-Person Capacity Temporary Horizontal Lifeline System (ANSI)

Model: UFA40110

60 ft. Adjustable 2-Person Temporary Horizontal Lifeline System with UFC401100 Carabiner and 2 O-Rings

60 FT. ADJUSTABLE TO SERVICE TO

DESIGN

- Housing made up of durable & high strength polymer
- Horizontal lifeline system easy to install, remove and store
- Light weight and portable design
- Inbuilt shock absorption mechanism to limit the impact forces during fall arrest
- Lifeline made up of Galvanized steel wire rope of Ø0.24 in. (6mm)
- Moulded handle use for easy to carry on job sites & metal handle for mounting
- To reel out the lifeline in free wheel mode, just pull the locking pin for easy installation
- Comes with Tension Indicator for correct amount of tension in lifeline

WIRE ROPE

Construction: 7X19 Galvanized steel wire Minimum Breaking Strength: 22 kN

SPAN LENGTH

59 ft. (18m)

NO. OF USERS

2

SYSTEM STRENGTH

Greater than 24 kN

CONFORMS TO

EN 795:2012, TYPE C & TS16415:2013 TYPE C

WEIGHT

 $31.72 \text{ lbs.} \pm 0.44 \text{ lbs.} (14.390 \text{ kgs} \pm 0.20 \text{ kgs}).$



