

Model: UFH10341G

KStrong® Kapture™ Epic+ 5-Point Full Body Harness, Enhanced Dorsal D-ring Plus™, Front D-ring, 2 Side D-rings, Waist Pad w/ Removable Tool Belt, Back/ Shoulder Pad, Trauma Relief Straps, QC Chest, TB Legs (ANSI)

5-Point FBH, Padded Waist w/Tool Belt, Back/Shoulder Pad, 1 Enhanced Dorsal D-ring, Front D-ring and 2 Side D-rings, QC Chest and TB Legs

DESIGN

- One dorsal attachment D-ring & one sternal D-Ring for fall arrest
- Adjustable shoulder, chest, and grommeted leg straps
- Waist belt for lumber support
- Grommetted leg straps

WEBBING

Material: Polyester

Width: 1.73 in. \pm 0.04 in. (44mm \pm 1mm)

Breaking Strength: 5000 lbs.

STITCHING THREAD


Material: High-tenacity Polyester


METAL COMPONENT

Material: Alloy Steel | Finish: PCB

RELEVANT STANDARDS

Meets or Exceeds ANSI Z359.11-2021





MODEL SIZE **WEIGHT** UFH10341G(S-M) $5.51 \text{ lbs.} \pm 0.02 \text{ lbs.}$ Small to Medium $(2500 \text{ gm} \pm 10 \text{ gm})$ $5.62 \text{ lbs.} \pm 0.02 \text{ lbs.}$ UFH10341G(M-L) Medium to Large $(2549 \text{ gm} \pm 10 \text{ gm})$ 5.73 lbs. ± 0.02 lbs. UFH10341G(L-XL) Large to X-Large $(2600 \text{ gm} \pm 10 \text{ gm})$ UFH10341G(XL-2XL) X-Large to $5.95 \text{ lbs.} \pm 0.02 \text{ lbs.}$ $(2699 gm \pm 10 gm)$



UFZ850100 Trauma

Relief Straps Included



Dorsal D-ring Plus™
Fast, easy, and safe
installation of dual
SRI connector.

STITCHING DESIGN