

Model: UFH10341G

KStrong® Kapture™ Epic 5-Point Full Body Harness, Enhanced Dorsal D-ring Plus™, Front D-ring, 2 Side D-rings, Waist Pad w/ Removable Tool Belt, Back/ Shoulder Pad, QC Chest and TB Legs - (ANSI)

5-Point FBH, Padded Waist w/Tool Belt, Back/Shoulder Pad, 1 Enhanced Dorsal D-ring, Front D-ring and 2 Side D-rings, QC Chest and TB Legs

п		•	74	а.	v
	-	-	ı	п.	v

- One dorsal attachment D-ring & one sternal D-Ring for fall arrest
- Adjustable shoulder, chest, and grommeted leg straps
- Waist belt for lumber support
- Grommetted leg straps

WEBBING

Material: Polyester

Width: 1.73 in. \pm 0.04 in. (44mm \pm 1mm)

Breaking Strength: 5000 lbs.

STITCHING THREAD


Material: High-tenacity Polyester


METAL COMPONENT

Material: Alloy Steel Finish: PCB

RELEVANT STANDARDS

Meets or Exceeds ANSI Z359.11-2014





BACK VIEW

 MODEL
 SIZE
 WEIGHT

 UFH10341G(S-M)
 Small to Medium
 5.51 lbs. ± 0.02 lbs. (2500 gm ±10 gm)

 UFH10341G(L-XL)
 Large to X-Large
 5.73 lbs. ± 0.02 lbs. (2600 gm ±10 gm)



Dorsal D-ring Plus™
Fast, easy, and safe installation of dual SRL connector.

STITCHING DESIGN