

Model: UFH10700P

KStrong® Kapture™ Element Arc Flash Rated 5-Point Full Body Harness, Dorsal D-ring, Mating Buckle Legs and Chest -(ANSI)

MODEL	SIZE	WEIGHT
UFH10700P(S-L)	Small to Large	$3.2 \text{ lbs.} \pm 0.02 \text{ lbs.}$ (1452 gm $\pm 10 \text{ gm}$)
UFH10700P(L-XL)	Large to X-Large	3.31 lbs. \pm 0.02 lbs. (1501 gm \pm 10 gm)

5-Point FBH - Dielectric Arc Flash Rated, Dorsal D-ring, PT Legs

DESIGN

- 5 Point adjustable full body harness made with FR webbing.
- Shoulder straps with Dielectric friction buckles for easy adjustment
- Chest straps & leg straps with Dielectric pass thru buckles for easy adjustment
- One back Dielectric D-Ring for fall arrest

WEBBING

Material: Aramid

Width: 1.73 in. \pm 0.04 in. (44mm \pm 1mm)

Breaking Strength: 5000 lbs.

STITCHING THREAD

Material: Kevlar

METAL COMPONENT

Material: Alloy Steel core with reinforced Polymer

Finish: Black Moulded

RELEVANT STANDARDS

Meets or Exceeds ANSI Z359.11-2021, ASTM F887-20



