KStrong® BRUTE™ Backer™ LE Dual 8.5 ft. SRL-LE with Tie-Back Hook (ANSI)

Model: UFS319006LD

Class

below dorsal D-ring

Dual assembly 8.5' Brute Backer Leading Edge (LE) Rated SRL with tie-back hooks at bottom and shock pack with connector at top

DESIGN

- Robust & durable plastic casing
- · Has swivel anchorage eye at anchorage end
- · Ultralight design almost unnoticeable on the users back
- Galvanized steel wire rope
- Twin legged tie-back SRL designed to be used in tie-back condition and near a potential leading edge as well
- Equipped with Twin SRL connector for direct connection to the dorsal attachment point of harness
- Tie-back snap hooks at the lanyard ends to make connection with anchor structure
- External shock pack design for added protection in leading edge application

CABLE

Material: Galvanized steel wire rope (Ø3/16") Minimum Breaking Strength: 3600 lbs.

WORKING LENGTH

8.5 Feet

WEIGHT

7.80 lbs. \pm 0.22 lbs. (3538 gm \pm 100 gm)

Meets or Exceeds ANSI Z359.14-2021 Class 2

RELEVANT STANDARDS

Shock Pack Tie back hook (PN 148)

Serial #:

Plastic casing O-Ring Heat shrink tube Polyester Webbing



Batch #: Date of First Use:

1-833-KSTRONG | KStrong.com