

KStrong® Side Entry Davit Assembly with Retrieval Device Bracket (High Strength Aluminum Alloy)

Model: UFT551080

DESIGN

- Ideal choice for access of confined space with help of Winches / Retrieval units, where regular anchorage system could not be used due to limited height constrained.
- Three adjustment points make it versatile to be used in various locations where anchor is at low level.
- Swivel eye at the end of cantilever to be attached to rated anchor point.
- Base with swivel pads for making the system level with the ground.
- Comes with preinstalled mounting brackets which are compatible with KStrong winches or retrieval blocks.
- It can be use for side gantry holes of confined space.
- Can also be used in both vertical & horizontal confined space entries.

PHYSICAL PARAMETERS

Body made up of high strength Aluminum Alloy

MAXIMUM LOAD CAPACITY

1102 lbs. (500kgs)

FINISH




Powder Coated in dual color - Black & Grey

SYSTEM STRENGTH

15 kN

WEIGHT

28.63 lbs. ± 0.22 lbs. (12.99kgs ± 0.10kgs)



Cantilever arm is adjustable at 3 defined points:

MINIMUM EXTENSION (79.41")

POSITION	REACH	HEIGHT
Lower	71.73"	47.44"
Middle	61.81"	82.99"
Upper	50.35"	97.68"

FULL EXTENSION (103.7")

POSITION	REACH	HEIGHT
Lower	95.98"	47.44"
Middle	88.58"	100.0"
Upper	67.51"	114.84"

Meets or Exceeds EN 795:2012 TYPE B

KStrong® BRUTE™ 60' Wire Cable 3-Way Rescue Retrieval SRL-R (ANSI)

Model: UFS310060R

KStrong® BRUTE™ 60' Wire Cable 3-Way Rescue Retrieval SRL-R with swivel eye at anchorage end, other end with load indicator swivel locking snap hook. Includes one (1) installation carabiner and one (1) tagline (ANSI)

BRUTE™

SRL SERIES

DESIGN

- Retrieval fall arrester block in polymer casing coupled with hoisting winch to enable easy retrieval of victim
- The locking pin on the side of the casing at the base of the handle allows this dual system to work in independent fall arrest & winch modes

LENGTH

60 ft.

PHYSICAL PARAMETERS

- Robust & durable plastic casing
- Has swivel anchorage eye at anchorage end
- Convenient inbuilt carry handle at anchorage end
- Steel swivel snap hook with load indicator at retractable end - gate strength 3600 lbs. (1633 kg)
- Galvanized steel wire rope

CABLE

Material: Galvanized steel wire rope Ø3/16"

MINIMUM BREAKING STRENGTH

3400 lbs. (1542 kg)

WEIGHT

22.38 lbs. ± 0.02 lbs. (10151 gm ± 10 gm)

RELEVANT STANDARDS


Meets or Exceeds ANSI Z359.14-2021 Class 1



Class

1

Anchor at or
above dorsal D-ring



Batch #: _____ Serial #: _____
Date of First Use: _____