

KStrong® EndurX™ 5-Point Full Body Harness, Abrasion Resistant Shoulder Pad, Deluxe Leg Pads, Enhanced Dorsal D-ring Plus™, Side D-rings, Quick Slide Adjusters, Trauma Relief Straps, QC Chest, TB Legs (SS), All Aluminum Hardware (ANSI)

Model: UFH10531G

EndurX
FULL BODY HARNESS

DESIGN

- Breathable Ultra Premium Shoulder Padding with Armor Hull™ and Ultra Premium Leg Padding equipped with Reflective Piping
- Stand-Up Dorsal D-ring with integrated Enhanced Dorsal D-ring+ for quick connection to SRL-P
- Suspension Trauma Straps integrated on cross sub-pelvic strap
- Compass™ Ready RFID tag for easy asset management
- D-ring configuration: 1 Dorsal, 2 Side Work Positioning
- Quick Connect Chest Buckle with Tongue Buckle Legs
- Quick Slide Torso Adjusters with no extra strapping left over (Patent Pending)
- Abrasion Resistant Shoulder Guards to better protect webbing when carrying materials

WEBBING

Material: Polyester
Width: 1.73 in. ± 0.04 in. (44mm ± 1mm)
Breaking Strength: 5000 lbs.

STITCHING THREAD

Material: High-tenacity Polyester

METAL COMPONENT

Material: Aluminum Hardware; Stainless Steel Grommets
Finish: Black Anodized


RELEVANT STANDARDS

Meets or Exceeds ANSI Z359.11-2021



MODEL	SIZE	WEIGHT
UFH10531G(XS)	XS	5.66 lbs. ± 5%
UFH10531G(S)	S	5.76 lbs. ± 5%
UFH10531G(M)	M	5.84 lbs. ± 5%
UFH10531G(L)	L	5.89 lbs. ± 5%
UFH10531G(XL)	XL	6.06 lbs. ± 5%
UFH10531G(2XL)	2XL	6.12 lbs. ± 5%
UFH10531G(3XL)	3XL	6.20 lbs. ± 5%



Front View



Back View



Stitching Design

AVL. Size : XS, S, M, L, XL, 2XL, 3XL

Batch #: _____ Serial #: _____

Date of First Use: _____