

KStrong® EndurX™ 5-Point Full Body Harness, Abrasion Resistant Shoulder Pad, Premium Work Positioning Waist Pad w/ Removable Tool Belt, Deluxe Leg Pads, Enhanced Dorsal D-ring Plus™, Front D-ring, Side D-rings, Premium Adjusters, Trauma Relief Straps, QC Chest, TB Legs (SS), All Aluminum Hardware (ANSI)

Model: UFH11512G



MODEL	SIZE	WEIGHT
UFH11512G(XS)	XS	7.46 lbs. ± 5%
UFH11512G(S)	S	7.57 lbs. ± 5%
UFH11512G(M)	M	7.69 lbs. ± 5%
UFH11512G(L)	L	7.92 lbs. ± 5%
UFH11512G(XL)	XL	8.10 lbs. ± 5%
UFH11512G(2XL)	2XL	8.28 lbs. ± 5%
UFH11512G(3XL)	3XL	9.31 lbs. ± 5%

DESIGN

- Breathable Ultra Premium Shoulder Padding with Armor Hull™ and Ultra Premium Leg Padding equipped with Reflective Piping
- Stand-Up Dorsal D-ring with integrated Enhanced Dorsal D-ring+ for quick connection to SRL-P
- Suspension Trauma Straps integrated on cross sub-pelvic strap
- Compass™ Ready RFID tag for easy asset management
- D-ring configuration: 1 Dorsal, 1 Sternal, 2 Side Work Positioning
- Quick Connect Chest Buckle with Tongue Buckle Legs
- Premium Torso Adjusters with no extra strapping left over
- Premium Work Positioning Waist Pad w/Removable Tool Belt equipped with 4 Tool Tether Tails
- Abrasion Resistant Shoulder Guards to better protect webbing when carrying materials

WEBBING

Material: Polyester
Width: 1.73 in. ± 0.04 in. (44mm ± 1mm)
Breaking Strength: 5000 lbs.

STITCHING THREAD



Material: High-tenacity Polyester

METAL COMPONENT

Material: Aluminum Hardware; Stainless Steel Grommets
Finish: Black Anodized

RELEVANT STANDARDS

Meets or Exceeds ANSI Z359.11-2021



Stitching Design
AVL. Size : XS, S, M, L, XL, 2XL, 3XL

Batch #: _____ Serial #: _____
Date of First Use: _____